

Residential Inverter R32 Heat Pump Console

Indoor Units

RAS-B10J2FVG-E

RAS-10J2FVG-TR

RAS-B13J2FVG-E

RAS-13J2FVG-TR

RAS-B18J2FVG-E

RAS-18J2FVG-TR

Outdoor Units

RAS-10J2AVSG-E / TR

RAS-13J2AVSG-E / TR


RAS-18J2AVSG-E / TR

Contents

1	Line up.	2
2	Specifications	3
3	Dimension	4
4	Wiring diagram	6
5	Refrigerant cycle diagram	8
6	Air Speed Distribution	11
7	Sound characteristics (NC Curve)	14
8	Capacity table	17
9	Part load performance	20
10	Performance characteristic	23

1. Line up

Indoor Unit	Outdoor Unit Common with SHORAI for single split	Model Name		Capacity Rank
		FCU	CDU (SHORAI)	
		RAS-B10J2FVG-E RAS-10J2FVG-TR	RAS-10J2AVSG-E RAS-10J2AVSG-TR	10k
		RAS-B13J2FVG-E RAS-13J2FVG-TR	RAS-13J2AVSG-E RAS-13J2AVSG-TR	13k
		RAS-B18J2FVG-E RAS-18J2FVG-TR	RAS-18J2AVSG-E RAS-18J2AVSG-TR	18k

Accessories	
	Refrigerant leak detection sensor RB-I301-E
	Standard remote controller WH-TA12LE
	Accessory wireless adapter RB-N104S-G Application : Toshiba Home AC Controller

2. Specifications

Model	Indoor		RAS-B10J2FVG-E RAS-10J2FVG-TR	RAS-B13J2FVG-E RAS-13J2FVG-TR	RAS-B18J2FVG-E RAS-18J2FVG-TR
	Outdoor		RAS-10J2AVSG-E RAS-10J2AVSG-TR	RAS-13J2AVSG-E RAS-13J2AVSG-TR	RAS-18J2AVSG-E RAS-18J2AVSG-TR
Power supply			(V/Ph/Hz) 220 - 240 / 1 / 50		
Cooling	Capacity (kW)		2.5 (0.95 - 3.2)	3.5 (1.05 - 4.1)	5.0 (1.2 - 5.6)
	Power Consumption (kW)		0.59 (0.21 - 0.90)	0.87 (0.27 - 1.20)	1.68 (0.34 - 2.00)
	EER		4.24	4.02	2.98
	PdesignC (kW)		2.50	3.50	5.00
	SEER		7.20	7.02	6.80
	Indoor Noise (H/L) (dB)		39/26	40/27	46/34
	Outdoor Noise (dB)		45	47	49
	Indoor Air Flow m³/min		8.2	8.8	10.0
Heating	Capacity (kW)		3.2 (0.85 - 4.40)	4.2 (1.00 - 5.00)	6.0 (1.3 - 6.3)
	Power Consumption (kW)		0.82 (0.18 - 1.25)	1.28 (0.22 - 1.55)	2.05 (0.31 - 2.20)
	COP		3.9	3.31	2.93
	PdesignH (Tbiv -7°C) (kW)		2.50	3.00	4.00
	SCOP		4.70	4.70	4.60
	Indoor Noise (H/L) (dB)		39/26	40/27	47/34
	Outdoor Noise (dB)		47	49	51
	Indoor Air Flow m³/min		8.2	9.2	11.0
FCU	Dimensions	H x W x D (mm)	600 x 700 x 220		
		Net Weigh (kg)	16	16	16
CDU	Dimensions	H x W x D (mm)	550 x 780 x 290		
		Net Weigh (kg)	26	30	34
Pipe	Chargeless (m)		15	15	15
	Maximum Length (m)		20	20	20
	Maximum Height (m)		12	12	12
	Refrigerant		R32		
	Refrigerant amount (kg)		0.55	0.80	1.10
Energy Label		Cooling / Heating	A++/A++		
Useble Range Temperature		Cooling (°C)	Indoor: 21 ~ 32 °C , Outdoor: (-15) ~ 46 °C		
		Heating (°C)	Indoor: 0 ~ 28 °C , Outdoor: (-15) ~ 24 °C		

For performance when each indoor unit is combined with other unit, refer to the separate table.

* The specifications may be subject to change without notice for purpose of improvement.








Cooling : Capacity test condition, inside : 27 °C (Db) / 19 °C (Wb), outside : 35 °C (Db) / 24 °C (Wb)

Heating : Capacity test condition, inside : 20 °C (Db), outside : 7 °C (Db) / 6 °C (Wb)

Piping length : 5 m per Indoor Unit.

Outdoor Unit : RAS-10J2AVSG-E / TR, RAS-13J2AVSG-E / TR, RAS-18J2AVSG-E / TR

(Unit : mm)




Installation dimension


4. Wiring diagrams

RAS-B10J2FVG-E1 / RAS-10J2FVG- TR : RAS-10J2AVSG-E/ TR

RAS-B13J2FVG-E1 / RAS-13J2FVG- TR : RAS-13J2AVSG-E/ TR




RAS-B18J2FVG-E / RAS-18J2FVG-TR : RAS-18J2AVSG-E / TR



5. Refrigerant Cycle Diagram


RAS-B10J2FVG-E / RAS-10J2FVG-TR : RAS-10J2AVG-E / TR



NOTE :

- The maximum pipe length of this air conditioner is 20 m. When the pipe length exceeds 15m, the additional charging of refrigerant, 20g per 1m for the part of pipe exceeded 15m is required. (Max. 100g)


RAS-B13J2FVG-E / RAS-13J2FVG-TR : RAS-13J2AVG-E / TR



NOTE :

- The maximum pipe length of this air conditioner is 20 m. When the pipe length exceeds 15m, the additional charging of refrigerant, 20g per 1m for the part of pipe exceeded 15m is required. (Max. 100g)

RAS-B18J2FVG-E / RAS-18J2FVG-TR : RAS-18J2AVG-E / TR




NOTE :

- The maximum pipe length of this air conditioner is 20 m. When the pipe length exceeds 15m, the additional charging of refrigerant, 20g per 1m for the part of pipe exceeded 15m is required. (Max. 100g)


6. Air Speed Distribution

RAS-B10J2FVG-E / RAS-10J2FVG-TR


Cooling - Upper & Lower




Cooling - Upper



Heating - Upper & Lower




Heating - Lower




RAS-B13J2FVG-E / RAS-13J2FVG-TR


Cooling - Upper & Lower




Cooling - Upper



Heating - Upper & Lower




Heating - Lower




RAS-B18J2FVG-E / RAS-18J2FVG-TR


Cooling - Upper & Lower




Cooling - Upper



Heating - Upper & Lower




Heating - Lower




7. Sound Characteristics (NC Curve)

RAS-10J2AVSG-E / TR (Rate : Hz)

Cooling




Heating




RAS-13J2AVSG-E / TR (Rate : Hz)

Cooling




Heating




RAS-18J2AVSG-E / TR (Rate : Hz)

Cooling



Heating



8. Capacity Table

Product models : RAS-B10J2FVG-E / RAS-10J2FVG-TR : RAS-10J2AVSG-E / TR

Specification of product at standard condition

Standard Condition	Indoor	27°C (DB) / 19°C (WB)	Total Cooling Capacity (TC)	2.50	kW
	Outdoor	35°C (DB) / 24°C (WB)	Sensible Heat Capacity (SHC)	2.00	kW

Outdoor air temperature DB (°C)	Indoor air temperature													
	20.0°C (DB) 14.0°C (WB)		23.0°C (DB) 16.0°C (WB)		26.0°C (DB) 18.0°C (WB)		27.0°C (DB) 19.0°C (WB)		28.0°C (DB) 20.0°C (WB)		30.0°C (DB) 22.0°C (WB)		32.0°C (DB) 24.0°C (WB)	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
20	2.45	2.11	2.70	2.25	2.90	2.39	2.98	2.39	3.07	2.38	3.25	2.36	3.40	2.32
21	2.42	2.09	2.68	2.22	2.86	2.36	2.95	2.36	3.03	2.36	3.21	2.34	3.36	2.29
22	2.40	2.06	2.65	2.20	2.83	2.34	2.92	2.33	3.00	2.33	3.18	2.31	3.32	2.27
23	2.37	2.04	2.62	2.17	2.80	2.31	2.89	2.31	2.97	2.31	3.14	2.29	3.29	2.24
24	2.34	2.02	2.59	2.15	2.77	2.29	2.85	2.28	2.93	2.28	3.11	2.26	3.25	2.22
25	2.32	1.99	2.56	2.13	2.74	2.26	2.82	2.26	2.90	2.26	3.07	2.23	3.21	2.19
26	2.29	1.97	2.53	2.10	2.71	2.23	2.79	2.23	2.87	2.23	3.04	2.21	3.18	2.17
27	2.26	1.95	2.50	2.08	2.68	2.21	2.76	2.21	2.84	2.20	3.00	2.18	3.14	2.14
28	2.24	1.93	2.47	2.05	2.65	2.18	2.72	2.18	2.80	2.18	2.97	2.16	3.10	2.12
29	2.21	1.90	2.44	2.03	2.62	2.16	2.69	2.15	2.77	2.15	2.93	2.13	3.07	2.09
30	2.19	1.88	2.41	2.01	2.58	2.13	2.66	2.13	2.74	2.13	2.90	2.11	3.03	2.07
31	2.16	1.86	2.38	1.98	2.55	2.11	2.63	2.10	2.70	2.10	2.86	2.08	2.99	2.04
32	2.13	1.84	2.36	1.96	2.52	2.08	2.60	2.08	2.67	2.08	2.83	2.06	2.96	2.02
33	2.11	1.81	2.33	1.93	2.49	2.05	2.56	2.05	2.64	2.05	2.79	2.03	2.92	1.99
34	2.08	1.79	2.30	1.91	2.46	2.03	2.53	2.03	2.60	2.02	2.76	2.01	2.88	1.97
35	2.05	1.77	2.27	1.88	2.43	2.00	2.50	2.00	2.57	2.00	2.72	1.98	2.85	1.94
36	2.03	1.74	2.24	1.86	2.40	1.98	2.47	1.97	2.54	1.97	2.69	1.95	2.81	1.92
37	2.00	1.72	2.21	1.84	2.37	1.95	2.44	1.95	2.51	1.95	2.65	1.93	2.78	1.89
38	1.97	1.70	2.18	1.81	2.34	1.93	2.40	1.92	2.47	1.92	2.62	1.90	2.74	1.87
39	1.95	1.68	2.15	1.79	2.30	1.90	2.37	1.90	2.44	1.90	2.58	1.88	2.70	1.84
40	1.92	1.65	2.12	1.76	2.27	1.87	2.34	1.87	2.41	1.87	2.55	1.85	2.67	1.82
41	1.90	1.63	2.09	1.74	2.24	1.85	2.31	1.85	2.37	1.84	2.51	1.83	2.63	1.79
42	1.87	1.61	2.06	1.72	2.21	1.82	2.28	1.82	2.34	1.82	2.48	1.80	2.59	1.77
43	1.84	1.59	2.03	1.69	2.18	1.80	2.24	1.79	2.31	1.79	2.44	1.78	2.56	1.74
44	1.82	1.56	2.01	1.67	2.15	1.77	2.21	1.77	2.27	1.77	2.41	1.75	2.52	1.72
45	1.79	1.54	1.98	1.64	2.12	1.75	2.18	1.74	2.24	1.74	2.37	1.73	2.48	1.69
46	1.76	1.52	1.95	1.62	2.09	1.72	2.15	1.72	2.21	1.72	2.34	1.70	2.45	1.67

Product models : RAS-B13J2FVG-E / RAS-13J2FVG-TR / RAS-13J2AVSG-E / TR

Specification of product at standard condition

Standard Condition	Indoor	27°C (DB) / 19°C (WB)	Total Cooling Capacity (TC)	3.50 kW
	Outdoor	35°C (DB) / 24°C (WB)	Sensible Heat Capacity (SHC)	2.70 kW

Outdoor air temperature DB (°C)	Indoor air temperature													
	20.0°C (DB) 14.0°C (WB)		23.0°C (DB) 16.0°C (WB)		26.0°C (DB) 18.0°C (WB)		27.0°C (DB) 19.0°C (WB)		28.0°C (DB) 20.0°C (WB)		30.0°C (DB) 22.0°C (WB)		32.0°C (DB) 24.0°C (WB)	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
20	3.43	2.85	3.79	3.04	4.05	3.23	4.17	3.22	4.29	3.21	4.55	3.18	4.76	3.11
21	3.39	2.82	3.75	3.01	4.01	3.19	4.13	3.19	4.25	3.18	4.50	3.14	4.70	3.07
22	3.35	2.79	3.70	2.97	3.97	3.16	4.08	3.15	4.20	3.15	4.45	3.11	4.65	3.04
23	3.32	2.76	3.66	2.94	3.92	3.12	4.04	3.12	4.15	3.11	4.40	3.07	4.60	3.01
24	3.28	2.73	3.62	2.91	3.88	3.09	3.99	3.08	4.11	3.08	4.35	3.04	4.55	2.97
25	3.24	2.70	3.58	2.87	3.84	3.06	3.95	3.05	4.06	3.04	4.30	3.01	4.50	2.94
26	3.21	2.67	3.54	2.84	3.79	3.02	3.90	3.01	4.02	3.01	4.25	2.97	4.45	2.91
27	3.17	2.64	3.50	2.81	3.75	2.99	3.86	2.98	3.97	2.97	4.20	2.94	4.40	2.87
28	3.13	2.61	3.46	2.78	3.71	2.95	3.81	2.94	3.92	2.94	4.16	2.90	4.35	2.84
29	3.10	2.58	3.42	2.74	3.66	2.92	3.77	2.91	3.88	2.90	4.11	2.87	4.29	2.81
30	3.06	2.55	3.38	2.71	3.62	2.88	3.72	2.87	3.83	2.87	4.06	2.83	4.24	2.77
31	3.02	2.52	3.34	2.68	3.57	2.85	3.68	2.84	3.78	2.83	4.01	2.80	4.19	2.74
32	2.99	2.48	3.30	2.65	3.53	2.81	3.63	2.80	3.74	2.80	3.96	2.77	4.14	2.71
33	2.95	2.45	3.26	2.61	3.49	2.78	3.59	2.77	3.69	2.76	3.91	2.73	4.09	2.67
34	2.91	2.42	3.22	2.58	3.44	2.74	3.54	2.73	3.65	2.73	3.86	2.70	4.04	2.64
35	2.87	2.39	3.17	2.55	3.40	2.71	3.50	2.70	3.60	2.70	3.81	2.66	3.99	2.61
36	2.84	2.36	3.13	2.51	3.36	2.67	3.46	2.67	3.55	2.66	3.76	2.63	3.94	2.57
37	2.80	2.33	3.09	2.48	3.31	2.64	3.41	2.63	3.51	2.63	3.71	2.60	3.89	2.54
38	2.76	2.30	3.05	2.45	3.27	2.60	3.37	2.60	3.46	2.59	3.67	2.56	3.83	2.50
39	2.73	2.27	3.01	2.42	3.23	2.57	3.32	2.56	3.42	2.56	3.62	2.53	3.78	2.47
40	2.69	2.24	2.97	2.38	3.18	2.53	3.28	2.53	3.37	2.52	3.57	2.49	3.73	2.44
41	2.65	2.21	2.93	2.35	3.14	2.50	3.23	2.49	3.32	2.49	3.52	2.46	3.68	2.40
42	2.62	2.18	2.89	2.32	3.09	2.46	3.19	2.46	3.28	2.45	3.47	2.42	3.63	2.37
43	2.58	2.15	2.85	2.29	3.05	2.43	3.14	2.42	3.23	2.42	3.42	2.39	3.58	2.34
44	2.54	2.12	2.81	2.25	3.01	2.40	3.10	2.39	3.18	2.38	3.37	2.36	3.53	2.30
45	2.51	2.09	2.77	2.22	2.96	2.36	3.05	2.35	3.14	2.35	3.32	2.32	3.48	2.27
46	2.47	2.05	2.73	2.19	2.92	2.33	3.01	2.32	3.09	2.31	3.27	2.29	3.42	2.24

Product models : RAS-B18J2FVG-E / RAS-18J2FVG-TR : RAS-18J2AVSG-E / TR

Specification of product at standard condition

Standard Condition	Indoor	27°C (DB) / 19°C (WB)	Total Cooling Capacity (TC)	5.00 kW
	Outdoor	35°C (DB) / 24°C (WB)	Sensible Heat Capacity (SHC)	3.50 kW

Outdoor air temperature DB (°C)	Indoor air temperature													
	20.0°C (DB) 14.0°C (WB)		23.0°C (DB) 16.0°C (WB)		26.0°C (DB) 18.0°C (WB)		27.0°C (DB) 19.0°C (WB)		28.0°C (DB) 20.0°C (WB)		30.0°C (DB) 22.0°C (WB)		32.0°C (DB) 24.0°C (WB)	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
20	4.90	3.73	5.41	3.95	5.79	4.20	5.96	4.17	6.13	4.15	6.49	4.07	6.79	3.95
21	4.84	3.69	5.35	3.91	5.73	4.15	5.90	4.13	6.07	4.11	6.43	4.03	6.72	3.91
22	4.79	3.65	5.29	3.87	5.67	4.11	5.83	4.08	6.00	4.06	6.36	3.99	6.65	3.87
23	4.74	3.61	5.23	3.83	5.60	4.06	5.77	4.04	5.94	4.02	6.29	3.94	6.57	3.83
24	4.69	3.57	5.18	3.78	5.54	4.02	5.71	3.99	5.87	3.98	6.22	3.90	6.50	3.78
25	4.63	3.53	5.12	3.74	5.48	3.97	5.64	3.95	5.80	3.93	6.15	3.85	6.43	3.74
26	4.58	3.49	5.06	3.70	5.42	3.93	5.58	3.90	5.74	3.89	6.08	3.81	6.35	3.70
27	4.53	3.45	5.00	3.66	5.36	3.88	5.51	3.86	5.67	3.84	6.01	3.77	6.28	3.66
28	4.48	3.41	4.94	3.61	5.29	3.84	5.45	3.81	5.61	3.80	5.94	3.72	6.21	3.61
29	4.42	3.37	4.88	3.57	5.23	3.79	5.39	3.77	5.54	3.75	5.87	3.68	6.14	3.57
30	4.37	3.33	4.83	3.53	5.17	3.75	5.32	3.72	5.47	3.71	5.80	3.64	6.06	3.53
31	4.32	3.29	4.77	3.49	5.11	3.70	5.26	3.68	5.41	3.66	5.73	3.59	5.99	3.48
32	4.27	3.24	4.71	3.44	5.04	3.66	5.19	3.63	5.34	3.62	5.66	3.55	5.92	3.44
33	4.21	3.20	4.65	3.40	4.98	3.61	5.13	3.59	5.28	3.57	5.59	3.50	5.84	3.40
34	4.16	3.16	4.59	3.36	4.92	3.57	5.06	3.54	5.21	3.53	5.52	3.46	5.77	3.36
35	4.11	3.12	4.54	3.32	4.86	3.52	5.00	3.50	5.14	3.48	5.45	3.42	5.70	3.31
36	4.05	3.08	4.48	3.27	4.79	3.48	4.94	3.46	5.08	3.44	5.38	3.37	5.62	3.27
37	4.00	3.04	4.42	3.23	4.73	3.43	4.87	3.41	5.01	3.39	5.31	3.33	5.55	3.23
38	3.95	3.00	4.36	3.19	4.67	3.39	4.81	3.37	4.94	3.35	5.24	3.28	5.48	3.19
39	3.90	2.96	4.30	3.15	4.61	3.34	4.74	3.32	4.88	3.30	5.17	3.24	5.40	3.14
40	3.84	2.92	4.24	3.10	4.55	3.30	4.68	3.28	4.81	3.26	5.10	3.20	5.33	3.10
41	3.79	2.88	4.19	3.06	4.48	3.25	4.62	3.23	4.75	3.22	5.03	3.15	5.26	3.06
42	3.74	2.84	4.13	3.02	4.42	3.20	4.55	3.19	4.68	3.17	4.96	3.11	5.18	3.02
43	3.66	2.79	4.05	2.96	4.33	3.14	4.46	3.12	4.59	3.11	4.86	3.05	5.08	2.96
44	3.56	2.71	3.94	2.88	4.22	3.06	4.34	3.04	4.46	3.02	4.73	2.96	4.94	2.88
45	3.23	2.46	3.56	2.61	3.82	2.77	3.93	2.75	4.04	2.74	4.28	2.68	4.48	2.61
46	3.14	2.39	3.47	2.54	3.71	2.69	3.82	2.68	3.93	2.66	4.17	2.61	4.36	2.54

10. Performance Characteristic


Model : RAS-B10J2FVG-E / RAS-10J2FVG-TR : RAS-10J2AVSG-E / TR

Product specification :

Condition		Capacity (kW)	Power (kW)	EER/COP
Cooling JIS In: 27 °C DB/19°C WB Out: 35°C DB/24°C WB	Min	0.95	0.21	4.52
	Rated	2.50	0.59	4.24
	Max	3.20	0.90	3.56
Heating JIS In: 20 °C DB/15°C WB Out: 7°C DB/6°C WB	Min	0.85	0.18	4.72
	Rated	3.20	0.82	3.90
	Max	4.40	1.25	3.52
Heating Low Temp. In: 20 °C DB/15°C WB Out: 2°C DB/1°C WB	Max	3.30	1.15	2.87
Heating Low Temp. In: 20 °C DB/15°C WB Out: -10°C DB	Max	2.40	1.100	2.18
Heating Low Temp. In: 20 °C DB/15°C WB Out: -15°C DB	Max	2.00	1.000	2.00


Cooling performance characteristic :

Outside Temp (°C)	Min capacity			Nominal capacity			Max capacity		
	Capacity (kW)	Power (kW)	EER (-)	Capacity (kW)	Power (kW)	EER (-)	Capacity (kW)	Power (kW)	EER (-)
20	1.13	0.16	6.87	2.98	0.46	6.44	3.82	0.71	5.40
21	1.12	0.17	6.68	2.95	0.47	6.25	3.77	0.72	5.25
22	1.11	0.17	6.49	2.92	0.48	6.08	3.73	0.73	5.10
23	1.10	0.17	6.30	2.89	0.49	5.91	3.69	0.75	4.96
24	1.08	0.18	6.13	2.85	0.50	5.74	3.65	0.76	4.82
25	1.07	0.18	5.96	2.82	0.51	5.58	3.61	0.77	4.68
26	1.06	0.18	5.79	2.79	0.51	5.43	3.57	0.78	4.55
27	1.05	0.19	5.63	2.76	0.52	5.28	3.53	0.80	4.43
28	1.04	0.19	5.48	2.72	0.53	5.13	3.49	0.81	4.31
29	1.02	0.19	5.33	2.69	0.54	4.99	3.45	0.82	4.19
30	1.01	0.19	5.19	2.66	0.55	4.86	3.41	0.84	4.08
31	1.00	0.20	5.05	2.63	0.56	4.73	3.36	0.85	3.97
32	0.99	0.20	4.91	2.60	0.56	4.60	3.32	0.86	3.86
33	0.97	0.20	4.78	2.56	0.57	4.47	3.28	0.87	3.75
34	0.96	0.21	4.65	2.53	0.58	4.35	3.24	0.89	3.65
35	0.95	0.21	4.52	2.50	0.59	4.24	3.20	0.90	3.56
36	0.94	0.21	4.40	2.47	0.60	4.12	3.16	0.91	3.46
37	0.93	0.22	4.28	2.44	0.61	4.01	3.12	0.93	3.37
38	0.91	0.22	4.17	2.40	0.62	3.91	3.08	0.94	3.28
39	0.90	0.22	4.06	2.37	0.62	3.80	3.04	0.95	3.19
40	0.89	0.23	3.95	2.34	0.63	3.70	2.99	0.96	3.10
41	0.88	0.23	3.84	2.31	0.64	3.60	2.95	0.98	3.02
42	0.86	0.23	3.74	2.28	0.65	3.50	2.91	0.99	2.94
43	0.85	0.23	3.64	2.24	0.66	3.41	2.87	1.00	2.86
44	0.84	0.24	3.54	2.21	0.67	3.32	2.83	1.02	2.79
45	0.83	0.24	3.45	2.18	0.67	3.23	2.79	1.03	2.71
46	0.82	0.24	3.36	2.15	0.68	3.14	2.75	1.04	2.64



Heating performance characteristic :

Outside Temp (°C)	Min capacity			Nominal capacity			Max capacity		
	Capacity (kW)	Power (kW)	COP (-)	Capacity (kW)	Power (kW)	COP (-)	Capacity (kW)	Power (kW)	COP (-)
-15	0.37	0.14	2.70	1.41	0.63	2.23	2.00	1.00	2.00
-14	0.39	0.14	2.75	1.46	0.64	2.27	2.08	1.02	2.04
-13	0.40	0.14	2.80	1.52	0.66	2.31	2.16	1.04	2.08
-12	0.42	0.15	2.85	1.57	0.67	2.35	2.24	1.06	2.11
-11	0.43	0.15	2.89	1.63	0.68	2.39	2.32	1.08	2.15
-10	0.45	0.15	2.94	1.69	0.69	2.43	2.40	1.10	2.18
-9	0.46	0.15	3.02	1.74	0.70	2.50	2.48	1.10	2.24
-8	0.48	0.15	3.10	1.79	0.70	2.56	2.55	1.11	2.30
-7	0.49	0.15	3.18	1.84	0.70	2.63	2.63	1.11	2.36
-6	0.50	0.15	3.26	1.90	0.70	2.69	2.70	1.12	2.42
-5	0.52	0.16	3.34	1.95	0.71	2.76	2.78	1.12	2.48
-4	0.53	0.16	3.41	2.00	0.71	2.82	2.85	1.13	2.53
-3	0.55	0.16	3.49	2.06	0.71	2.88	2.93	1.13	2.59
-2	0.56	0.16	3.57	2.11	0.72	2.95	3.00	1.13	2.65
-1	0.57	0.16	3.64	2.16	0.72	3.01	3.08	1.14	2.70
0	0.59	0.16	3.72	2.21	0.72	3.07	3.15	1.14	2.76
1	0.60	0.16	3.79	2.27	0.72	3.13	3.23	1.15	2.81
2	0.62	0.16	3.87	2.32	0.73	3.20	3.30	1.15	2.87
3	0.68	0.16	4.13	2.36	0.74	3.20	3.36	1.17	2.88
4	0.74	0.17	4.38	2.39	0.75	3.21	3.43	1.19	2.88
5	0.81	0.17	4.62	2.43	0.75	3.22	3.49	1.21	2.89
6	0.83	0.18	4.67	3.12	0.81	3.86	4.29	1.23	3.48
7	0.85	0.18	4.72	3.20	0.82	3.90	4.40	1.25	3.52
8	0.87	0.18	4.77	3.28	0.83	3.94	4.51	1.27	3.56
9	0.89	0.19	4.82	3.37	0.85	3.98	4.63	1.29	3.59
10	0.92	0.19	4.86	3.45	0.86	4.02	4.74	1.31	3.62
11	0.94	0.19	4.91	3.53	0.87	4.05	4.85	1.33	3.66
12	0.96	0.19	4.95	3.61	0.88	4.09	4.97	1.35	3.69
13	0.98	0.20	4.99	3.70	0.90	4.12	5.08	1.37	3.72
14	1.00	0.20	5.03	3.78	0.91	4.16	5.19	1.39	3.75
15	1.03	0.20	5.07	3.86	0.92	4.19	5.31	1.40	3.78
16	1.05	0.21	5.11	3.94	0.93	4.22	5.42	1.42	3.81
17	1.07	0.21	5.14	4.03	0.95	4.25	5.54	1.44	3.83
18	1.09	0.21	5.18	4.11	0.96	4.28	5.63	1.46	3.86
19	1.11	0.21	5.22	4.19	0.97	4.31	5.69	1.46	3.90
20	1.14	0.22	5.25	4.27	0.99	4.34	5.74	1.46	3.94
21	1.16	0.22	5.28	4.36	1.00	4.37	5.79	1.46	3.97
22	1.18	0.22	5.32	4.44	1.01	4.39	5.84	1.46	4.01
23	1.20	0.22	5.35	4.52	1.02	4.42	5.89	1.46	4.04
24	1.22	0.23	5.38	4.60	1.04	4.44	5.94	1.46	4.08




Model : RAS-B13J2FVG-E / RAS-13J2FVG-TR : RAS-13J2AVSG-E / TR

Product specification :

Condition		Capacity (kW)	Power (kW)	EER/COP
Cooling JIS In: 27 °C DB/19°C WB Out: 35°C DB/24°C WB	Min	1.05	0.27	3.89
	Rated	3.50	0.87	4.02
	Max	4.10	1.20	3.42
Heating JIS In: 20 °C DB/15°C WB Out: 7°C DB/6°C WB	Min	1.00	0.22	4.55
	Rated	4.20	1.27	3.31
	Max	5.00	1.55	3.23
Heating Low Temp. In: 20 °C DB/15°C WB Out: 2°C DB/1°C WB	Max	3.50	1.30	2.69
Heating Low Temp. In: 20 °C DB/15°C WB Out: -10°C DB	Max	2.60	1.100	2.36
Heating Low Temp. In: 20 °C DB/15°C WB Out: -15°C DB	Max	2.20	1.000	2.20


Cooling performance characteristic :

Outside Temp. (°C)	Min capacity			Nominal capacity			Max capacity		
	Capacity (kW)	Power (kW)	EER (-)	Capacity (kW)	Power (kW)	EER (-)	Capacity (kW)	Power (kW)	EER (-)
20	1.25	0.21	5.91	4.17	0.68	6.11	4.89	0.94	5.19
21	1.24	0.22	5.74	4.13	0.70	5.94	4.84	0.96	5.04
22	1.23	0.22	5.58	4.08	0.71	5.77	4.78	0.98	4.90
23	1.21	0.22	5.42	4.04	0.72	5.61	4.73	0.99	4.76
24	1.20	0.23	5.27	3.99	0.73	5.45	4.68	1.01	4.63
25	1.18	0.23	5.12	3.95	0.75	5.30	4.63	1.03	4.50
26	1.17	0.24	4.98	3.90	0.76	5.15	4.57	1.05	4.38
27	1.16	0.24	4.84	3.86	0.77	5.01	4.52	1.06	4.26
28	1.14	0.24	4.71	3.81	0.78	4.87	4.47	1.08	4.14
29	1.13	0.25	4.58	3.77	0.80	4.74	4.42	1.10	4.03
30	1.12	0.25	4.46	3.72	0.81	4.61	4.36	1.11	3.92
31	1.10	0.25	4.34	3.68	0.82	4.49	4.31	1.13	3.81
32	1.09	0.26	4.22	3.63	0.83	4.37	4.26	1.15	3.71
33	1.08	0.26	4.11	3.59	0.85	4.25	4.21	1.17	3.61
34	1.06	0.27	4.00	3.54	0.86	4.13	4.15	1.18	3.51
35	1.05	0.27	3.89	3.50	0.87	4.02	4.10	1.20	3.42
36	1.04	0.27	3.78	3.46	0.88	3.92	4.05	1.22	3.33
37	1.02	0.28	3.68	3.41	0.89	3.81	3.99	1.23	3.24
38	1.01	0.28	3.59	3.37	0.91	3.71	3.94	1.25	3.15
39	1.00	0.29	3.49	3.32	0.92	3.61	3.89	1.27	3.07
40	0.98	0.29	3.40	3.28	0.93	3.51	3.84	1.29	2.98
41	0.97	0.29	3.31	3.23	0.94	3.42	3.78	1.30	2.90
42	0.96	0.30	3.22	3.19	0.96	3.33	3.73	1.32	2.83
43	0.94	0.30	3.13	3.14	0.97	3.24	3.68	1.34	2.75
44	0.93	0.30	3.05	3.10	0.98	3.15	3.62	1.35	2.68
45	0.92	0.31	2.96	3.05	0.99	3.07	3.42	1.26	2.71
46	0.90	0.31	2.89	3.01	1.01	2.98	3.35	1.26	2.65



Heating performance characteristic :

Outside Temp. (°C)	Min capacity			Nominal capacity			Max capacity		
	Capacity (kW)	Power (kW)	COP (-)	Capacity (kW)	Power (kW)	COP (-)	Capacity (kW)	Power (kW)	COP (-)
-15	0.46	0.15	3.04	1.91	0.86	2.21	2.20	1.00	2.20
-14	0.47	0.15	3.09	1.98	0.88	2.25	2.28	1.02	2.24
-13	0.49	0.16	3.14	2.05	0.90	2.28	2.36	1.04	2.27
-12	0.51	0.16	3.18	2.12	0.92	2.32	2.44	1.06	2.30
-11	0.52	0.16	3.23	2.19	0.93	2.35	2.52	1.08	2.33
-10	0.54	0.16	3.27	2.26	0.95	2.38	2.60	1.10	2.36
-9	0.55	0.17	3.31	2.33	0.97	2.41	2.68	1.12	2.40
-8	0.57	0.17	3.35	2.39	0.98	2.44	2.75	1.13	2.43
-7	0.58	0.17	3.40	2.46	0.99	2.47	2.83	1.15	2.46
-6	0.60	0.17	3.44	2.52	1.01	2.50	2.90	1.17	2.49
-5	0.62	0.18	3.48	2.59	1.02	2.53	2.98	1.18	2.51
-4	0.63	0.18	3.51	2.65	1.04	2.56	3.05	1.20	2.54
-3	0.65	0.18	3.55	2.72	1.05	2.58	3.13	1.22	2.57
-2	0.66	0.18	3.59	2.78	1.07	2.61	3.20	1.23	2.59
-1	0.68	0.19	3.62	2.85	1.08	2.64	3.28	1.25	2.62
0	0.69	0.19	3.66	2.91	1.10	2.66	3.35	1.27	2.64
1	0.71	0.19	3.69	2.98	1.11	2.68	3.43	1.28	2.67
2	0.72	0.19	3.72	3.04	1.12	2.71	3.50	1.30	2.69
3	0.80	0.20	3.98	3.09	1.14	2.72	3.55	1.29	2.75
4	0.87	0.21	4.22	3.14	1.15	2.72	3.60	1.28	2.81
5	0.95	0.21	4.45	3.19	1.17	2.73	3.64	1.27	2.87
6	0.97	0.22	4.50	4.09	1.25	3.27	4.87	1.53	3.19
7	1.00	0.22	4.55	4.20	1.27	3.31	5.00	1.55	3.23
8	1.03	0.22	4.59	4.31	1.29	3.34	5.13	1.57	3.26
9	1.05	0.23	4.64	4.42	1.31	3.37	5.26	1.60	3.29
10	1.08	0.23	4.68	4.53	1.33	3.40	5.39	1.62	3.32
11	1.10	0.23	4.72	4.63	1.35	3.44	5.52	1.65	3.35
12	1.13	0.24	4.76	4.74	1.37	3.47	5.65	1.67	3.38
13	1.15	0.24	4.80	4.85	1.39	3.49	5.77	1.69	3.41
14	1.18	0.24	4.84	4.96	1.41	3.52	5.90	1.72	3.44
15	1.21	0.25	4.88	5.07	1.43	3.55	6.03	1.74	3.46
16	1.23	0.25	4.92	5.18	1.45	3.58	6.16	1.77	3.49
17	1.26	0.25	4.95	5.28	1.47	3.60	6.29	1.79	3.51
18	1.28	0.26	4.99	5.39	1.49	3.63	6.42	1.81	3.54
19	1.31	0.26	5.02	5.50	1.51	3.65	6.55	1.84	3.56
20	1.34	0.26	5.05	5.61	1.53	3.68	6.68	1.86	3.59
21	1.36	0.27	5.09	5.72	1.55	3.70	6.81	1.89	3.61
22	1.39	0.27	5.12	5.83	1.56	3.72	6.94	1.91	3.63
23	1.41	0.27	5.15	5.93	1.58	3.74	7.06	1.93	3.65
24	1.44	0.28	5.18	6.04	1.60	3.77	7.15	1.95	3.68




Model : RAS-B18J2FVG-E / RAS-18J2FVG-TR : RAS-18J2AVSG-E / TR

Product specification :

Condition		Capacity (kW)	Power (kW)	EER/COP
Cooling JIS In: 27 °C DB/19°C WB Out: 35 °C DB/24°C WB	Min	1.20	0.34	3.53
	Rated	5.00	1.68	2.98
	Max	5.60	2.00	2.80
Heating JIS In: 20 °C DB/15°C WB Out: 7 °C DB/6°C WB	Min	1.30	0.31	4.19
	Rated	6.00	2.05	2.93
	Max	6.30	2.20	2.86
Heating Low Temp. In: 20 °C DB/15°C WB Out: 2 °C DB/1°C WB				
	Max	4.80	1.80	2.67
	Max	3.30	1.440	2.29
Heating Low Temp. In: 20 °C DB/15°C WB Out: -10 °C DB				
	Max	2.80	1.350	2.07
	Max	2.80	1.350	2.07


Cooling performance characteristic :

Outside Temp (°C)	Min capacity			Nominal capacity			Max capacity		
	Capacity (kW)	Power (kW)	EER (-)	Capacity (kW)	Power (kW)	EER (-)	Capacity (kW)	Power (kW)	EER (-)
20	1.43	0.27	5.36	5.96	1.32	4.52	6.68	1.57	4.25
21	1.42	0.27	5.21	5.90	1.34	4.39	6.61	1.60	4.13
22	1.40	0.28	5.06	5.83	1.37	4.27	6.53	1.63	4.02
23	1.38	0.28	4.92	5.77	1.39	4.15	6.46	1.66	3.90
24	1.37	0.29	4.78	5.71	1.42	4.03	6.39	1.68	3.79
25	1.35	0.29	4.65	5.64	1.44	3.92	6.32	1.71	3.69
26	1.34	0.30	4.52	5.58	1.46	3.81	6.25	1.74	3.59
27	1.32	0.30	4.40	5.51	1.49	3.71	6.17	1.77	3.49
28	1.31	0.31	4.28	5.45	1.51	3.61	6.10	1.80	3.39
29	1.29	0.31	4.16	5.39	1.54	3.51	6.03	1.83	3.30
30	1.28	0.32	4.05	5.32	1.56	3.41	5.96	1.86	3.21
31	1.26	0.32	3.94	5.26	1.58	3.32	5.89	1.89	3.12
32	1.25	0.33	3.83	5.19	1.61	3.23	5.82	1.91	3.04
33	1.23	0.33	3.73	5.13	1.63	3.14	5.74	1.94	2.96
34	1.22	0.34	3.63	5.06	1.66	3.06	5.67	1.97	2.88
35	1.20	0.34	3.53	5.00	1.68	2.98	5.60	2.00	2.80
36	1.18	0.34	3.43	4.94	1.70	2.90	5.53	2.03	2.73
37	1.17	0.35	3.34	4.87	1.73	2.82	5.46	2.06	2.65
38	1.15	0.35	3.25	4.81	1.75	2.74	5.38	2.09	2.58
39	1.14	0.36	3.17	4.74	1.78	2.67	5.31	2.11	2.51
40	1.12	0.36	3.08	4.68	1.80	2.60	5.24	2.14	2.44
41	1.11	0.37	3.00	4.61	1.83	2.53	5.17	2.17	2.37
42	1.09	0.37	2.92	4.54	1.86	2.46	5.10	2.20	2.30
43	1.08	0.38	2.84	4.47	1.89	2.39	5.03	2.23	2.23
44	1.06	0.38	2.77	4.40	1.92	2.33	4.96	2.26	2.16
45	1.05	0.39	2.69	4.33	1.95	2.27	4.89	2.29	2.09
46	1.03	0.39	2.62	4.26	1.98	2.21	4.82	2.32	2.02



Heating performance characteristic :

Outside Temp (°C)	Min capacity			Nominal capacity			Max capacity		
	Capacity (kW)	Power (kW)	COP (-)	Capacity (kW)	Power (kW)	COP (-)	Capacity (kW)	Power (kW)	COP (-)
-15	0.55	0.21	2.67	2.54	1.36	1.86	2.80	1.35	2.07
-14	0.57	0.21	2.73	2.63	1.38	1.91	2.90	1.37	2.12
-13	0.59	0.21	2.79	2.72	1.40	1.95	3.00	1.39	2.16
-12	0.61	0.21	2.84	2.81	1.42	1.98	3.10	1.40	2.21
-11	0.63	0.22	2.90	2.90	1.43	2.02	3.20	1.42	2.25
-10	0.65	0.22	2.95	2.99	1.45	2.06	3.30	1.44	2.29
-9	0.67	0.22	3.00	3.10	1.48	2.09	3.43	1.47	2.33
-8	0.70	0.23	3.05	3.22	1.51	2.13	3.55	1.50	2.37
-7	0.72	0.23	3.09	3.33	1.54	2.16	3.68	1.53	2.40
-6	0.75	0.24	3.14	3.44	1.57	2.19	3.80	1.56	2.44
-5	0.77	0.24	3.18	3.56	1.60	2.22	3.93	1.59	2.47
-4	0.79	0.25	3.22	3.67	1.63	2.25	4.05	1.62	2.50
-3	0.82	0.25	3.26	3.78	1.66	2.27	4.18	1.65	2.53
-2	0.84	0.26	3.30	3.89	1.69	2.30	4.30	1.68	2.56
-1	0.87	0.26	3.33	4.01	1.72	2.33	4.43	1.71	2.59
0	0.89	0.27	3.37	4.12	1.75	2.35	4.55	1.74	2.61
1	0.92	0.27	3.40	4.23	1.78	2.37	4.68	1.77	2.64
2	0.94	0.27	3.43	4.35	1.81	2.40	4.80	1.80	2.67
3	1.04	0.28	3.67	4.42	1.84	2.40	4.90	1.81	2.70
4	1.14	0.29	3.89	4.49	1.86	2.41	4.99	1.82	2.74
5	1.23	0.30	4.10	4.56	1.89	2.42	5.09	1.84	2.77
6	1.27	0.31	4.15	4.65	1.92	2.43	5.19	1.86	2.80
7	1.30	0.31	4.19	4.74	1.95	2.44	5.29	1.88	2.83
8	1.33	0.31	4.24	4.83	1.98	2.45	5.39	1.90	2.86
9	1.37	0.32	4.28	4.92	2.01	2.46	5.49	1.92	2.89
10	1.40	0.32	4.32	5.01	2.04	2.47	5.59	1.94	2.92
11	1.43	0.33	4.36	5.10	2.07	2.48	5.69	1.96	2.95
12	1.47	0.33	4.39	5.19	2.10	2.49	5.79	1.98	2.98
13	1.50	0.34	4.43	5.28	2.13	2.50	5.89	2.00	3.01
14	1.53	0.34	4.47	5.37	2.16	2.51	5.99	2.02	3.04
15	1.57	0.35	4.50	5.46	2.19	2.52	6.09	2.04	3.07
16	1.60	0.35	4.54	5.55	2.22	2.53	6.19	2.06	3.10
17	1.64	0.36	4.57	5.64	2.25	2.54	6.29	2.08	3.13
18	1.67	0.36	4.60	5.73	2.28	2.55	6.39	2.10	3.16
19	1.70	0.37	4.63	5.82	2.31	2.56	6.49	2.12	3.19
20	1.74	0.37	4.66	5.91	2.34	2.57	6.59	2.14	3.22
21	1.77	0.38	4.69	6.00	2.37	2.58	6.69	2.16	3.25
22	1.80	0.38	4.72	6.09	2.40	2.59	6.79	2.18	3.28
23	1.84	0.39	4.75	6.18	2.43	2.60	6.89	2.20	3.31
24	1.87	0.39	4.78	6.27	2.46	2.61	6.99	2.22	3.34



TOSHIBA CARRIER (THAILAND) CO.,LTD.

144/9 Moo 5, Bangkadi Industrial Park, Tivanon Road, Tambol Bangkadi,
Amphur Muang, Pathumthani 12000, Thailand

Copyright © 2015 TOSHIBA CARRIER (THAILAND), All Rights Reserved

Notice : Toshiba is committed to continuously improving its products to ensure the highest quality and reliability standard, and to meet local regulations and market requirements. All features and specifications are subject to change without prior notice.
